



# BZYW.R39952 - CAULKING AND SEALANTS

## Caulking and Sealants

See General Information for Caulking and Sealants

**AEROSEAL LLC**

R39952

225 Byers Rd

Miamisburg, OH 45342 USA

Type Aerobarrier X1 sealant applied at a maximum rate of 9 g/ft<sup>2</sup> (wet), for optional for use in L500, M500, P500, U300, V300 and W300 Series assemblies to create an air barrier.

Material shall be installed per the manufacturer's installation instructions accompanying the finished product.

The product has not been investigated to provide a degree of fire resistance to openings in fire-resistive walls, floors or ceilings under Fill, Void or Cavity Materials (XHHW).

Last Updated on 2019-12-09

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"